

THE F.A.I.T. (FIELD AIR INSPECTION TOOL)

"INSULATING EQUIPMENT SHALL BE INSPECTED FOR DAMAGE BEFORE EACH DAY'S USE AND IMMEDIATELY FOLLOWING ANY INCIDENT THAT CAN REASONABLY BE SUSPECTED OF CAUSING DAMAGE. INSULATING GLOVES SHALL BE GIVEN AN AIR TEST, ALONG WITH THE INSPECTION." - FROM OSHA 1910.137(C)(2)(II)

USED FOR **DAILY** VISUAL AIR INSPECTION OF RUBBER GLOVES



WORKS WITH ANY SIZE GLOVE

11" GLOVES REQUIRE ADDITIONAL AIR TO BE BLOWN INTO GLOVES BEFORE ROLLING, TO FULLY INFLATE & INSPECT THE GLOVE

INSPECT BOTH GLOVES IN LESS THAN 2 MINUTES

SCREEN PRINTED LOGOS AVAILABLE

HOW TO USE: Slide the cuff of the glove into the gap of the FAIT. Roll the glove over & around the FAIT to create a tight seal for better air retention & superior visual inspection of your rubber gloves. Flip gloves inside out & repeat.



*VISIT OUR WEBSITE AT WWW.HJARNETT.COM/FAIT TO SEE A VIDEO DEMONSTRATION.

A QUICK, INEXPENSIVE WAY TO VERIFY THE INTEGRITY OF INSULATING RUBBER GLOVES!



Part# HJA-750

SAFETY | SERVICE | SAVINGS



INDUSTRY LEADERS IN ELECTRICAL TESTING & PRODUCTS FOR UTILITIES & COMMUNICATIONS



20460 SW AVERY COURT, TUALATIN, OR 97062
PHONE (503) 692-4600 • FAX (503) 692-4661

WWW.HJARNETT.COM
INFORMATION@HJARNETT.COM